DI-1522 • DI-2323 • DIL-2323 Drop-in Series



Servend.





- Servend's patented flex manifold makes carbonated or non-carbonated drink changes possible in minutes.
- Easy service access with no tools required to remove drain pan, splash panel, and ice bin door.
- Front accessible cold plate inlets for easy installation.
- Flomatic 464GP beverage valves enhance drink quality and presentation.
- Dual view merchandiser highlights brand offering from all sides.



Leader in Ice & Beverage Dispensers

Countertop Ice/Bev • Drop-in • Countertop Electric Undercounter • Beverage Towers • Ice Chests



DI-1522 • DI-2323 • DIL-2323 Drop-in Series

Specifications			
	DI-1522	DI-2323	DIL-2323
Standard Features	Dual-view merchandiser, light kit. "Quench Your Thirst" graphics, key switch and drain kit.		
Ice Storage Capacity	Up to 65 lbs. / 29 kgs.	Up to 77 lbs. / 35 kgs.	Up to 97 lbs. / 44.1 kgs.
Flex Manifold	2-1-1-2 right to left	3-1-1-1-2 right to left	
Electrical Requirements	120V/60Hz/2.4FLA 220V/50Hz/1 also available	120V/60Hz/3.2FLA 220V/50Hz/1 also available	
Drain	One recessed 3/4" (1.91 cm) FPT is located on the bottom of unit. A second recessed 3/4" (1.91 cm) FPT drain connection for the drain pan is located adjacent to the cold plate drain.		
Approx. Shipping Weights	162 lbs. / 73.5 kgs.	191 lbs. / 86.8 kgs.	195 lbs. / 88.6 kgs.
Countertop Weight (w/o ice)	69.2 lbs. / 31.4 kgs.	88.5 lbs. / 40.2 kgs.	96.5 lbs. / 43.9 kgs.
Valves	Flomatic 464GP valves are available in sanitary lever, push button, portion control and automatic fill valves. Valve lockout switch on ice bin door available. Other valves available, contact factory for details.		
Options	Drop-in tower light box and splash guards.		













