

# Flavor Magic™ Drink Enhancement System



Servend.



Flomatic's Flavor Magic™ Drink Enhancement System allows you to offer your fountain beverage customers more flavor choices without using any additional counter space.

- Flavor Magic™ System is compatible with all MDH-Series, SV-Series, and S-Series ice/ beverage dispensers.
- Valve components are based on proven Flomatic technology.
- Blue LED backlit dispense nozzle draws attention to product.
- Built-in dispense counter allows usage data to be retrieved from control board.

- Available pre-installed on new equipment or in easy-to-install retrofit kits to add flavor flexibility to existing equipment.
- Retrofit kits contain all the necessary components, including the syrup rack and pumps.
- Flavor Magic System is available in 3 or 4 flavors with single control module and 3, 4, 6 and 8 flavors with dual control modules. Dual control module systems are compatible with MDH-302 and MDH-402 dispensers only.



ISO 9001:2000  
Quality System Certified

**Leader in Ice & Beverage Dispensers**

Countertop Ice/Bev • Drop-in • Countertop Electric  
Undercounter • Beverage Towers • Ice Chests

**Manitowoc**  
Foodservice Group

# Flavor Magic™ Drink Enhancement System

## Specifications

<b>Standard Features</b>	Portion control through adjustable dispense time, backlit dispense nozzle with field-selectable flash sequence, built-in dispense counter to track individual flavor sales, POP static cling instruction sheet, easy-to-install pre-assembled valve/control board module.
<b>Flavor Magic Module Kit Contents</b>	Switch cover with nozzle, ice chute bracket, cover mounting bracket, internal nozzle tubing mount, control board and valve solenoid assembly, nozzle LED
<b>Back Room Kit Contents</b>	BIB rack, BIB syrup pumps (1 for each flavor), low pressure CO2 regulator (0-100 PSI), 50 feet of bundled tubing (1 tube for each flavor)
<b>BIB Rack Dimensions W x H x D</b>	1 X 3 rack: 20" x 36" x 19"; 1 X 4 rack: 20" x 48" x 19"; 2 X 3 rack: 32" x 36" x 19"; 2 X 4 rack: 32" x 48" x 19"
<b>Electrical</b>	24VAC, 0.5 AMP, powered by existing valve transformer on dispenser
<b>Flavors Dispensed</b>	3 or 4 per module
<b>Flow Rate</b>	Variable, 0.5 oz/sec nominal
<b>Dispense Time</b>	0.2 - 10 seconds, adjustable in 0.2 second increments
<b>Inlet Pressure Range</b>	10 - 40 PSI

3306C ©2007 Servend 707 Continuing product improvement may necessitate change of specifications without notice.



MANITOWOC BEVERAGE  
EQUIPMENT, INC.  
2100 Future Drive  
Sellersburg, IN 47172, USA  
Ph: 812-246-7000 • Fax: 812-246-7024  
Visit us online at [www.manitowocbeverage.com](http://www.manitowocbeverage.com)

